

39 140 000 **RAPID SL ELEMENT FOR WC, 1.13 M INSTALLATION HEIGHT WITH FIXING ELEMENT FOR BACK SUPPORT AND SUPPORT RAILS**



A	1080	1130
B	230	280
C	910	960
D	950	1000
E	1010	1060

PRODUCT DESCRIPTION

- With flushing cistern GD 2, 6 - 9 l
- For the disabled
- For WC bowls 70 cm projection
- For on-the-wall installations or studded walls
- Powder coated steel frame, self-supporting
- For dry-cladding, completely pre-assembled
- With fixed connections
- quick adjustment, lockable
- Fixing material
- TÜV approved
- 2 WC fixing bolts
- 4 wall brackets
- Fixing device for ceramic
- Distance of fixing bolts 180/230 mm
- PP outlet bend Ø 90 mm
- Depth adjustable
- PP reducer Ø 90/110 mm
- Inlet and outlet connecting set
- Flushing cistern GD 2, 6 - 9 l, containing following features:
 - Adjustment ex factory 6 l and 3 l
 - Pneumatic discharge valve offering 3 modes of operation: dual flush or start/stop or single flush
- Water supply from left/right or back
- Low noise (group I acc. to German Noise Specification)
- Insulated against condensation
- ½" water supply connection including integrated angle valve and push fit flexible hose union
- No tools required for the installation of the inspection shaft including protection during construction phase
- For vertical or horizontal use
- Including wall brackets 38 558 00M for on-the-wall installation
- For mounting of small flush plates please order revision shaft 40 911 000 (sold separately)

39 140 000 **RAPID SL ELEMENT FOR WC, 1.13 M INSTALLATION HEIGHT WITH FIXING ELEMENT FOR BACK SUPPORT AND SUPPORT RAILS**



SPARE PARTS, June 2014 – now

- 1: Threaded screw (Spare part-nr. 4276400M)
- 2: WC inlet and outlet connecting set (Spare part-nr. 37311K00)
- 2.1: Bath faucet fastener (Spare part-nr. 43511SH0)
- 2.2: Connector (Spare part-nr. 37119000)
- 3: PP-outlet elbow (DN 90) (Spare part-nr. 42327000)
- 4: 4" Outlet Adaptor F Rapid SL (Spare part-nr. 42242000)
- 5: Support for outlet (Spare part-nr. 42243000)
- 6: Inspection shaft (Spare part-nr. 66791000)
- 7: Filling valve (Spare part-nr. 37095000)
- 7.1: Lever (Spare part-nr. 43734000)
- 7.1.1: Seal (Spare part-nr. 4377000M)
- 7.2: Valve head (Spare part-nr. 43536000)
- 7.3: Membrane (Spare part-nr. 4375800M)
- 7.4: Screw cap (Spare part-nr. 43735000)
- 7.5: Valve float (5 pcs) (Spare part-nr. 4379100M)
- 7.6: Set of seals (Spare part-nr. 43722000)*
- 8: Support unit (Spare part-nr. 42246000)
- 9: Connection tube (Spare part-nr. 42233000)
- 9.1: O-ring (Spare part-nr. 0319100M)
- 10: Cartridge (Spare part-nr. 42385000)
- 11: Dual Flush discharge valve AV1 (Spare part-nr. 42320000)
- 11.1: extension for Overflow pipe (Spare part-nr. 42313000)
- 11.2: pneumatic hose (Spare part-nr. 42319000)
- 11.3: Seal (Spare part-nr. 42310000)
- 12: Valve seat for GD2 (Spare part-nr. 42315000)
- 13: Wall brackets (Spare part-nr. 3855800M)
- 14: Set for noise protection (Spare part-nr. 37131000)*
- 15: Adapter (Spare part-nr. 38796000)*
- 16: 4.5 l adapter for GD2 (Spare part-nr. 42333000)*
- 17: Radio electronic (Spare part-nr. 39141000)*
- 18: Radio electronic (Spare part-nr. 38759SD0)*
- 19: Radar (868,4 MHz) (Spare part-nr. 38758000)*
- 20: Radio transmitter (Spare part-nr. 39142000)*
- 21: WC control for manual remote actuation (Spare part-nr. 38934SD0)*
- 22: Flush plate (Spare part-nr. 38564000)*
- 23: Pneumatic actuation
(Spare part-nr. 37059000)*

* Optional accessories